

**MODEL TES-1326/1327**

- °C / □ Selectable
- Back-light LCD display
- Laser targeting
- Emissivity adjustable (1327)
- Audible and visible alarm (1327)
- Data memory and read function (1327)
- Maximum / Minimum function



**FEATURES:**

- 0.1□/0.2□ Resolution
- -20°C ~ 500°C
- Built-in Laser Sighting/Backlight LCD display
- Memory / Read logging Capacity (50 Sets) (1327)
- Adjustable emissivity (1327)
- Adjustable / Visible Alarm (1327)
- MAX / MIN Reading

**SPECIFICATIONS:**

<b>Display</b>	Backlight LCD display
<b>Measurement Range</b>	-20°C ~ 500°C (-4□ ~ 932□)
<b>Resolution</b>	0.1°C / 0.2□ (1327)
<b>Resolution</b>	<100°: 0.1°C / 0.2□ , >100°: 1°C / 1□ (1326)
<b>Accuracy</b>	± 2% reading or ± 2°C
<b>Spectral Response</b>	6 ~ 14µm
<b>Field of View</b>	8:1 optics ratio with a 1" min target
<b>Emissivity</b>	0.1 ~ 1.0 , (1326 : fixed 0.95)
<b>Auto power off</b>	approx. 15 sec
<b>Sighting</b>	Laser marker 1mw

<b>Data memory capacity</b>	50 sets (Direct reading from LCD display) (1327)
<b>Battery Life</b>	50hrs
<b>Power Source</b>	One 9V cell (ANSI/NEDA-1604A, IEC-6LR61)
<b>Operating / Storage Condition</b>	0°C ~ 50°C (32° ~ 122°) below 80%RH -10°C ~ 60°C (14° ~ 140°) below 70%RH
<b>Dimensions</b>	170mm × 118mm × 46mm
<b>Weight</b>	200g
<b>Accessories</b>	Instruction manual, Battery